




EVERLIGHT ELECTRONICS CO., LTD.

Device Number: DPT-038-094 REV: 1.0
ODEL NO: PT383-3C ECN: Page: 1/7

Package Dimensions:



Office: NO 25,Lane.76, Chung Yang Rd., Sec.3, Tucheng, Taipei 236, Taiwan, R.O.C.

TEL: 886-2-2267-2000,2267-9936(22Lines)

FAX: 886-2-2267-6189

http: [//www.everlight.com](http://www.everlight.com)



EVERLIGHT ELECTRONICS CO., LTD.

Device Number: DPT-038-094 REV: 1.0
MODEL NO: PT383-3C ECN: Page: 2/7

©Notes :

- 1.All dimensions are in millimeter.
- 2.Protruded resin under flange 1.5 mm Max.
- 3.Lead spacing is measured where the lead emerge from the package.
- 4.Lens color : Water clear.
- 5.Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
- 6.These specification sheets include materials protected under copyright of EVERLIGHT corporation . Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.
- 7.When using this product , please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.

Description

PT383-3C is a high speed and high sensitive NPN silicon phototransistor molded in a standard $\phi 5$ mm package . Due to its water clear epoxy the device is sensitive to visible and near infrared radiation .

Features

- High photo sensitivity
- Fast response time

Applications

- Optoelectronic switch
- VCR ,Video camera
- Floppy disk drive



Device Number: DPT-038-094 REV: 1.0
MODEL NO: PT383-3C ECN: Page: 3/7

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Collector-Emitter Voltage	V_{CEO}	30	V
Emitter-Collector Voltage	V_{ECO}	5	V
Collector Current	I_C	20	mA
Operating temperature Range	Topr	-25 to +85	°C
Storage Temperature Range	Tstg	-40 to +85	°C
Lead Soldering Temperature (1/16 inch from body for 5 sec.)	Tsol	260	°C
Power Dissipation at (or below) 25°C Free Air Temperature	Pc	100	mW







Electro Optical Characteristics (Ta=25°C)

Parameter	Symbol	MIN	TYP	MAX	Unit	Condition
Collector-Emitter Breakdown Voltage	BV_{CEO}	30	---	---	V	$I_C=1mA$ $E_e=0mW/cm^2$
Emitter-Collector Breakdown Voltage	BV_{ECO}	5	---	---	V	$I_E=100uA$ $E_e=0mW/cm^2$
Collector-Emitter Saturation Voltage	$V_{CE(s)}$	---	---	0.4	V	$I_C=80uA$ $E_e=1mW/cm^2$
Rise Time	t_r	---	15	---	uS	$V_{CE}=5V$ $I_C=1mA$ $R_L=1000\Omega$
Fall Time	t_f	---	15	---		
Collector Dark Current	I_{CEO}	---	---	100	nA	$V_{CE}=20V$ $E_e=0mW/cm^2$
On state Collector Current	$I_{C(on)}$	1.0	4.0	---	mA	$V_{CE}=5V$ $E_e=1mW/cm^2$
Wavelength of Peak Sensitivity	λ_p	---	860	---	nm	
Rang of Spectral Bandwidth	λ_p	400	---	1200	nm	



Device Number: DPT-038-094 REV: 1.0
MODEL NO: PT383-3C ECN: Page: 4/7

Typical Electrical/Optical/Characteristics Curves





EVERLIGHT ELECTRONICS CO., LTD.

MODEL NO: PT383-3C Device Number: DPT-038-094 REV: 1.0
ECN: Page: 5/7

Reliability

The reliability of products shall be satisfied with items listed below.

Confidence level : 90%


LTPD : 10%

Test Items	Test Conditions	Failure Judgement Criteria	Samples(n)
			Defective(c)
Operation life	V _{CE} =5V , Ta : 25℃ 1000hrs	$I_{C(on)} \leq L \times 0.8$ L : Lower specification limit	n =22 , c=0
Temperature cycle	1 cycle -55℃ to +25℃ to +85℃ (30min) (5min) (30min) 50 cycle test		n =22 , c=0
Thermal shock	-10℃ to +100℃ (5min) (10sec) (5min) 50cycle test		n =22 , c=0
High temperature storage	Temp : +100℃ 1000hrs		n =22 , c=0
Low temperature storage	Temp : -55℃ 1000hrs		n =22 , c=0
High temperature High humidity	Ta : 85℃ RH : 85% 1000hrs		n =22 , c=0
Solder heat	Temp : 260 ± 5℃ 5sec 4mm Form the bottom of the package.		n =22 , c=0
Solderability	Temp : 230 ± 5℃ 5sec 4mm Form the bottom of the package.	More than 90% of Lead to be covered by soldering	n =22 , c=0



Test Method For Power

Condition : $E_e=1\text{m W/c m}^2$, $V_{CE}=5\text{V}$
Test Item : Collector Current (unit : mA)



Supplements

1.Parts
(1) Chip

Type	Material	Wavelength of Peak Sensitivity
PT	Silicon	860nm

(2) Material


Type	Lead frame	Wire	Package
Material	SPCC	Gold	Epoxy



EVERLIGHT ELECTRONICS CO., LTD.

Device Number: DPT-038-094 REV: 1.0
MODEL NO: PT383-3C ECN: Page: 7/7

Packing Specifications



CPN : Customer's Production Number
P/N : Production Number
QTY : Packing Quantity
CAT : Ranks
HUE : Peak Wavelength
REF : Reference
LOT NO : Lot Number
MADE IN TAIWAN : Production Place

Packing Quantity Specification

1.500Pcs/1Bag , 6Bags/1Box

2.10Boxes/1Carton